

Our Newest Shuttle Station Machine

MOLD⁺MAN™ 6200 Product Specification Sheet

Dimensions & Weight

Height	1829 mm / 72"
Width	889 mm / 35"
Depth	1168 mm / 46"
Weight	450 kg / 1000 lbs

Power & Air Requirements

Voltage	230 VAC, Single Phase, 50/60Hz, 30A
Air Pressure	8 bar / 116 psi
Air Volume	180 lpm / 6 SCFM

Standard Features

Clamp	Pneumatic
Clamping Force	20 kn / 2 ton
Clamp Stroke	150 mm / 6"
Ejector	Pneumatic
Ejector Force	1535 N / 345 lbf
Ejector Stroke	10 mm / 0.4"
Shuttle Table	Yes
Shuttle Table Stroke	400 mm / 15.75"
Mold-set Dimension	Mold 220 mm x 180 mm / 8.7" x 7.1"
Thickness	150 mm / 6"
Shot Size	0.5-100 g / 0.02-3.0 oz
Mold-set Cooling	Yes
Melt Reservoir	8 kg / 17.6 lbs
Melt Temperature	Up to 245 °C / 475 °F
Melt Capacity	8.2 kg/h / 18 lbs/h
Pump Motor	400 W / .5 HP
Injection Pressure	1-30 bar / 15-450 psi
Operator Display	Touch screen, micro processor controlled

Safety Features	Emergency-stop button
------------------------	-----------------------

Mold-Man® 6200 Options

Double Clamping Cylinder Mold-set Cooling Kit.
Kit includes chiller, hoses and fittings

OVERMOULD™

Wpkv 6. Eqoogteg Yc . Ngkijvqp Dw||ctf. NW9 6YT

ucngu qxgtoqwnf0eqo
+44 (0) 1525 373800
<https://www.overmould.com>